

FUJIFILM
expect INNOVATION™

HA PREMIER



**DIGI
POWER**

QuickZoom

HAs18x7.6B RM/RD

Technology That Inspires...

FUJINON

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
1-800-284-2288 sales@avsupply.com
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

HAs18x7.6B RM/RD*




Zoom Ratio / Format	18X / 2/3"
Focal Length	7.6 to 137 mm
Maximum Relative Aperture	1:1.8 (7.6 ~ 103 mm)
Angular Field of View	7.6 mm 64° 30' x 39° 03'
16:9 Aspect Ratio	137 mm 4° 01' x 2° 15'
M.O.D. from Image Plane	0.84 m
M.O.D. from Front of Lens	0.6 m
Object Dimensions at M.O.D.	7.6 mm 738 x 415 mm 137 mm 41 x 23 mm
Filter Size	ø 82 mm P=0.75 (On Barrel)
Dia ø x Length (w/o Hood)	ø85 x 204 mm
Weight (w/o Hood)	1.26 kg / 1.33 kg*
Options	16 Bit Encoder
Features	Inner Focus

*RD contain servos for zoom and focus.

ACCESSORIES: HD & SD ENG/EFP


THREE-MODE FINE FOCUS

By shifting the sensitivity from the wide side to the telephoto side of the focus range, this control provides more precise focusing for studio or sports productions.




SERIAL DIGITAL REMOTE CONTROL BY PC

Remote control of zoom, focus and iris for Digipower lenses is possible via serial digital link, providing accurate positioning for virtual studio and other applications requiring digital precision.



DIGI ZOOM DEMAND*



*New Digital features only available on ERM/ERD-M/S.

- A. CFC-990 Flex Cable
- B. FMM-3B/6B Manual Module
- C. ZMM-6 Manual Module
- D. EBF-1 Focus Cable
- E. MCA-6
- F. ERD-20A-A02 Zoom Demand
- G. FSP-13G Focus Positional Module
- H. EPD-4A-E02
- I. CZH-14 Focus Handle
- J. CFH-11 Focus Handle
- K. MCA-7 Mounting Clamp
- L. EPD-20A-A01/A02 Focus Demand
- M. ERD-10A-D01 Zoom Demand
- N. ALH-117A-02A Support for HA36x/A36x HA42x




Note: ERD-20A-A02 (F) and EPD-20A-A02 (L) replace the ERD-T22 and EPD-2CA.

DIGI POWER REAR CONTROL KITS


MS-11D Manual Focus/Servo Zoom

For use with RM/ZM type lenses.




SS-11D Servo Focus/Servo Zoom

For use with RM/ZM type lenses.




SS-13D Servo Focus/Servo Zoom

For use with RD/ZD type lenses.




SS-14S Servo Focus/Servo Zoom

For use with RD/ZD type lenses.




STANDARD REAR CONTROL KITS

MS-11 Manual Focus/Servo Zoom




SS-11 Servo Focus/Servo Zoom

Not available on HA42x, HA36x and A36




SS-13A Servo Focus/Servo Zoom

For use with ERD type lenses.



MM-11 Manual Focus/Manual Zoom

Not available on HA42x, HA36x and A36x



*Specify camera type

**FMM-3C for use on HA36x, HA42x and HA25x

MOUNTING SYSTEM

Fujinon has replaced the "cone" shaped mounting system with the "tooth" system. The cone type may still be ordered as a special order.



ACCESSORIES: HD ENG/EFP


LENS CONVERTERS



HD/ENG LENS CONVERTERS

Model	Type	ø Size	Converter*	Mag.	Converted Focal Length (mm)	M.O.D. (m)	Weight (kg)
HS16x4.6	TELE	95 mm	TCV-H95	1.5x	74.0→111.0	0.90	1.0
	WIDE	95 mm	WCV-H95	0.8x	4.6→3.9	0.29	1.0
HS18x5.5/ HS18x5.5	TELE	85 mm	TCV-H85	1.5x	100.0→150.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	5.5→4.4	0.38	1.0
	WIDE	85 mm	WAT-H85	0.7x	5.5→3.9	0.29	0.3
	FISHEYE	85 mm	F-ATH85	0.57x	5.5→3.1	0.19	0.3
HA16x6.3	TELE	95 mm	TCV-H95	1.5x	101.0→152.0	0.90	1.0
	WIDE	95 mm	WCV-H95	0.8x	6.3→5.4	0.29	1.0
HA18x7.6E/ HA18x7.6	TELE	85 mm	TCV-H85	1.5x	137.0→205.5	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	7.6→6.1	0.38	1.0
	WIDE	85 mm	WAT-H85	0.7x	7.6→5.3	—	0.3
	FISHEYE	85 mm	F-ATH85	0.57x	—	—	0.3
HA22x7.3E	TELE	110 mm	TCV-H110	1.5x	161.0→242.0	1.90	1.1
	WIDE	110 mm	WCV-H100	1.5x	175.0→262.5	1.80	1.0
HA23x7.6E	TELE	100 mm	TCV-H100	0.8x	7.6→6.1	0.51	1.0
	WIDE	100 mm	WAT-H100	0.7x	7.6→5.3	0.39	0.5
	FISHEYE	100 mm	F-ATH100	0.57x	7.6→4.3	0.26	0.6
XS17x5.5	TELE	85 mm	TCV-H85	1.5x	94.0→141.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	5.5→4.4	0.38	1.0
	WIDE	85 mm	WAT-H85	0.7x	5.5→3.9	0.29	0.3
	FISHEYE	85 mm	F-ATH85	0.57x	5.5→3.1	0.19	0.3
ZA17x7.6	TELE	85 mm	TCV-H85	1.5x	130.0→195.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	7.6→6.1	0.38	1.0
	WIDE	85 mm	WAT-H85	0.7x	7.6→5.3	0.29	0.3
	FISHEYE	85 mm	F-ATH85	0.57x	7.6→4.3	0.19	0.3
ZA22x7.6	TELE	100 mm	TCV-H100	1.5x	167.0→250.5	1.80	1.0
	WIDE	100 mm	WCV-H100	0.8x	7.6→6.1	0.51	1.0
	WIDE	100 mm	WAT-H100	0.7x	7.6→5.3	0.39	0.5
	FISHEYE	100 mm	F-ATH100	0.57x	7.6→4.3	0.26	0.6

*TCV/WCV are zoom thru type **ø 95mm P-1 screw on type
Wide attachment and fisheye attachment can be used at WIDE END.
Number of M.O.D. is at wide end.



For Sales Contact Information go to
www.Fujinon.com

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101